

UNCLASSIFIED

AD NUMBER

AD821664

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited. Document partially illegible.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors; Critical Technology; OCT 1967. Other requests shall be referred to Air Force Technical Application Center, Washington, DC. Document partially illegible. This document contains export-controlled technical data.

AUTHORITY

usaf ltr, 28 feb 1972

THIS PAGE IS UNCLASSIFIED

AD821664

**TFSO LONG-PERIOD L-ARRAY  
NOISE COHERENCE**

**20 October 1967**

**Prepared For**

**AIR FORCE TECHNICAL APPLICATIONS CENTER  
Washington, D. C.**

**By**

**E. F. Chiburis  
TELEDYNE, INC.**

**Under**

**Project VELA UNIFORM**

**Sponsored By**

**ADVANCED RESEARCH PROJECTS AGENCY  
Nuclear Test Detection Office  
ARPA Order No. 624**

**BEST  
AVAILABLE COPY**

TFSO LONG-PERIOD L-ARRAY  
NOISE COHERENCE

SEISMIC DATA LABORATORY REPORT NO. 199

AFTAC Project No.:	VELA T/6702
Project Title:	Seismic Data Laboratory
ARPA Order No.:	624
ARPA Program Code No.:	5810
Name of Contractor:	TELEDYNE, INC.
Contract No.:	F 33657-67-C-1313
Date of Contract:	2 March 1967
Amount of Contract:	\$ 1,736,617
Contract Expiration Date:	1 March 1968
Project Manager	William C. Dean (703) 836-7644

P. O. Box 334, Alexandria, Virginia

AVAILABILITY

This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.

This research was supported by the Advanced Research Projects Agency, Nuclear Test Detection Office, under Project VELA-UNIFORM and accomplished under the technical direction of the Air Force Technical Applications Center under Contract F 33657-67-C-1313.

Neither the Advanced Research Projects Agency nor the Air Force Technical Applications Center will be responsible for information contained herein which may have been supplied by other organizations or contractors, and this document is subject to later revision as may be necessary.

## TABLE OF CONTENTS

	Page No.
ABSTRACT	
INTRODUCTION	1
ORDINARY COHERENCE	1
Noise Sample #1	1
Noise Sample #2	2
Noise Sample #3	3
MULTIPLE COHERENCE	3
RECORDED SIGNALS	4
CONCLUSIONS	5
REFERENCES	6

## ILLUSTRATIONS

### Figure

1. Location Map of the TFSO L-array.
2. Ordinary Coherence Between TFO and PY1, PY2, PY3, PY4, PY5. Noise Sample #1.
3. Ordinary Coherence Between PY1 and PY2, PY3, PY4, PY5. Noise Sample #1.
4. Ordinary Coherence Between PY2 and PY3, PY4, PY5. Noise Sample #1.
5. Ordinary Coherence Between PY3 and PY4, PY5, and Between PY4 and PY5. Noise Sample #1.
6. Power Spectra at the TFSO L-array for Noise Sample #1.
7. Ordinary Coherence Between TFO and PY1, PY2, PY3, PY4 for Lag Windows of 200 Points. Noise Sample #1.
8. Ordinary Coherence Between PY1 and PY2, PY3, PY4, PY5 for Lag Windows of 200 Points. Noise Sample #1.
9. Ordinary Coherence Between PY2 and PY3, PY4, PY5 for Lag Windows of 200 Points. Noise Sample #1.
10. Ordinary Coherence Between TFO and PY1, PY2, PY4 and Between PY1 and PY2 For Lag Windows of 400 Points. Noise Sample #1.
11. Ordinary Coherence Between TFO and PY1, PY2, PY3, PY4, PY5, With Tight Filter. Noise Sample #1.
12. Ordinary Coherence Between PY1 and PY2, PY3, PY4, PY5, With Tight Filter. Noise Sample #1.
13. Ordinary Coherence Between PY2 and PY3, PY4, PY5, With Tight Filter. Noise Sample #1.
14. Ordinary Coherence Between PY3 and PY4, PY5, and Between PY4 and PY5 With Tight Filter. Noise Sample #1.

## ILLUSTRATIONS

(continued)

### Figure

15. Ordinary Coherence Between TFO and PY1, PY2, PY4, PY5. Noise Sample #2.
16. Ordinary Coherence Between PY1 and PY2, PY4, PY5. Noise Sample #2.
17. Ordinary Coherence Between PY2 and PY4, PY5 and Between PY4 and PY5. Noise Sample #2.
18. Power Spectra At The TFSO L-array for Noise Sample #2.
19. Ordinary Coherence Between TFO and PY1, PY2, PY3, PY4. Noise Sample #3.
20. Ordinary Coherence Between PY1 and PY2, PY3, PY4, PY5. Noise Sample #3.
21. Ordinary Coherence Between PY2, and PY3, PY4, PY5. Noise Sample #3.
22. Ordinary Coherence Between PY3 and PY4, PY5 and Between PY4 and PY5. Noise Sample #3.
23. Multiple Coherence With TFO As Output and PY1 through PY5 as Inputs. Noise Sample #1 (upper) and Noise Sample #3 (lower).
24. Large Love-Wave Signals Recorded At The TFSO L-array.



## ABSTRACT

Three long-period noise samples recorded at the TFSO L-array were analyzed for coherence properties. The results indicate that the ordinary coherence is generally high between elements 5-10 km apart and low between elements further apart. Multiple coherence is high for the first noise sample but low for the third sample.

Zero-delay noise summations for an additional sample produce about  $N^{1/2}$  improvement over the average RMS noise level and beam-forming of a large P-wave signal produces about  $N^{1/2}$  improvement in signal-to-noise ratio.

## INTRODUCTION

During the period from about 01 February 1967 to 06 April 1967, a six-element array of long period seismographs was operated in the vicinity of the Tonto Forest Seismological Observatory in Arizona. The L-shaped array was composed of two legs bearing ENE and SSE with lengths approximately 25 km and 15 km respectively (Figure 1). Each of the sites contained three-component Geotech Model 7505A vertical and 8700C horizontal seismometers (free periods of 20 sec); photo-cell amplifiers were at all sites except TFSO which has a standard photo-tube amplifier.

The purpose of the array was to record and analyze the spatial properties (coherence) of long-period noise in the vicinity of TFSO with a view towards installing a permanent long-period 40 km hexagonal array of seven elements.

## ORDINARY COHERENCE

Noise samples from three different time periods were used for computing ordinary coherence. These samples, designated "Noise Sample #1" through "Noise Sample #3", are from the following time periods:

Noise Sample #1 - 25 February 67	0801Z
Noise Sample #2 - 26 March 1967	1025Z
Noise Sample #3 - 05 April 1967	1330Z

Noise Sample #1. This sample contains 4000 points digitized (by Geotech) at two points per second and prefiltered with a band-pass of 0.01 cps to 0.30 cps (half-power) with 18 db/octave rolloff. The ordinary coherences vs. frequency between all pairs of seismometers are shown in Figures 2 through 5. These coherences were obtained using a lag window of 50 points. As shown on these figures, the site PY-5 appears to have noise which is incoherent with the other sites. It is believed that there were no instrumental difficulties with this site (data are normal, visually, and the auto-spectrum agrees with the spectra from the other sites, as shown in




FIGURE 1. LOCATION MAP OF THE TFSO L-ARRAY.




FIGURE 2. ORDINARY COHERENCE BETWEEN TFO AND PY1, PY2, PY3, PY4, PY5. NOISE SAMPLE #1.




FIGURE 3. ORDINARY COHERENCE BETWEEN PY1 AND  
PY2 PY3 PY4 PY5




FIGURE 4. ORDINARY COHERENCE BETWEEN PY2 AND




FIGURE 5. ORDINARY COHERENCE BETWEEN PY3 and PY4, PY5 AND BETWEEN PY4 AND PY5. NOISE SAMPLE #1

Figure 6) so that the noise at this site is perhaps due to local winds, site emplacement properties, etc. Subsequent noise coherences from different times will be shown which indicate similar properties at PY-5 and to a lesser extent at PY-4 and PY-3.

Additional coherences were computed from the same data, but with lag windows of 200 points, for various (not all) pairs (Figures 7, 8, and 9) and of 400 points (Figure 10). There are no significant changes in the computed coherences using the longer lag lengths, except those anticipated, such as a general increase in coherence with the longer lag windows (see, for example, Chiburis and Dean, 1967a, b, c, d).

The characteristics of the bandpass filter applied to the data used for the results shown in Figures 2 through 10 (0.01 cps to 0.30 cps, 18 db/octave rolloff) were changed to 0.017 cps to 0.200 cps, 12 db/octave rolloff and coherences recomputed to note any effects due to filtering. Figures 11 through 14 show the coherence results of the tighter bandpass filter. The only significant differences occur at the higher frequencies, as expected, with more instability in computing the coherence.

Noise Sample #2. This sample contains 2910 points at one point per second (digitized at five points per second and decimated) pre-filtered from 0.010 cps to 1.00 cps (24 db/octave) and then low-pass filtered with a high-cut of 0.50 cps. Ten-percent lags were used (290 points). The results for six pairs are shown in Figures 15 through 17. The noise between the array sites for this particular sample appears highly incoherent, generally remaining below 0.50 at the lower frequencies. This result suggests that a simple array summation should suppress the noise by a factor of  $N^{1/2}$ . A computer program, LOPSAN, is available at SDL (R. A. Hartenberger, personal communication) that measures the RMS noise level (and signal levels as well) of array data before and after summing, or beamforming. Root-mean-square noise measurements from data recorded on 12 February 1967 at 0730Z, 0750Z, and 0810Z were made to determine the amount of






FIGURE 6. POWER SPECTRA AT THE TFSO L-ARRAY FOR NOISE SAMPLE #1.




FIGURE 7. ORDINARY COHERENCE BETWEEN TFO AND PY1, PY2, PY3, PY4 FOR LAG WINDOWS OF 200 POINTS. NOISE SAMPLE #1.




FIGURE 8. ORDINARY COHERENCE BETWEEN PY1 AND PY2, PY3, PY4, PY5 FOR LAG WINDOWS OF 200 POINTS. NOISE SAMPLE #1.




FIGURE 9. ORDINARY COHERENCE BETWEEN PY2 AND PY3, PY4, PY5 FOR LAG WINDOWS OF 200 POINTS. NOISE SAMPLE #1.




FIGURE 10. ORDINARY COHERENCE BETWEEN TFO AND PY1, PY2, PY4, AND BETWEEN PY1 AND PY2 FOR LAG WINDOWS OF 400 POINTS. NOISE SAMPLE #1.




FIGURE 11. ORDINARY COHERENCE BETWEEN TFO AND PY1, PY2, PY3, PY4, PY5 WITH TIGHT FILTER. NOISE SAMPLE #1.




FIGURE 12. ORDINARY COHERENCE BETWEEN PY1 AND PY2, PY3, PY4, PY5 WITH TIGHT FILTER. NOISE SAMPLE #1.




FIGURE 13. ORDINARY COHERENCE BETWEEN PY2 AND PY3, PY4, PY5 WITH TIGHT FILTER. NOISE SAMPLE #1.




FIGURE 14. ORDINARY COHERENCE BETWEEN PY3, AND PY4, PY5, AND BETWEEN PY4 AND PY5 WITH TIGHT FILTER. NOISE SAMPLE #1.




FIGURE 15. ORDINARY COHERENCE BETWEEN TFO AND PY1, PY2, PY4, PY5. NOISE SAMPLE #2.




FIGURE 16. ORDINARY COHERENCE BETWEEN PY1 AND PY2, PY4, PY5. NOISE SAMPLE #2.




FIGURE 17. ORDINARY COHERENCE BETWEEN PY2 AND PY4, PY5, AND BETWEEN PY4 AND PY5. NOISE SAMPLE #2.

noise improvement possible with a zero-delay summation. This recording date was selected on the basis of high apparent noise background. Two combinations of array elements were used in the summations. The following table gives these results.

Time Sample	Elements	Avg.RMS*	Summation RMS	Improvement	
				db	$N^{\frac{1}{2}}$ db
0730-0750	TFO, PY1, 2, 3, 4, 5	47.66	21.01	7.1	7.8
0730-0750	TFO, PY1, 2, 4, 5	46.98	22.02	6.6	7.0
0750-0810	TFO, PY1, 2, 3, 4, 5	47.82	18.84	8.1	7.8
0750-0810	TFO, PY1, 2, 4, 5	47.01	21.89	6.6	7.0
0810-0830	TFO, PY1, 2, 3, 4, 5	58.93	25.13	7.4	7.8
0810-0830	TFO, PY1, 2, 4, 5	57.97	26.24	6.9	7.0

\*Each data trace was "demagnified" by an arbitrary value to yield about the same individual RMS level.

The data recorded at PY3 appeared to be questionable so array summations were made both with and without PY3 data. The improvement results in either case are close to the predicted  $N^{\frac{1}{2}}$ db indicating that the noise is spatially uncorrelated for zero-delay summations.

The spectra for Noise Sample #2 at five of the array sites is shown in Figure 18.

Noise Sample #3. This sample contains 3574 points (digitized at one point per second), band-passed from 0.017 cps to 0.500 cps (12 db/octave), and low-passed with a high-cut at 0.35 cps. Again, 10% lags (360 points) were used.

The results for all station pairs are shown in Figures 19 through 22.

## MULTIPLE COHERENCE

Multiple coherences as a function of frequency were computed for Noise Samples #1 and #3. Multiple coherence indicates the number of input data channels which would be necessary to describe a noise field and gives a quantitative measure, versus frequency, of how well a linear combination of these  $n$  input channels can match the  $(n + 1)$ st channel. The selected output channel for both noise samples was TFO and the inputs were PY1 through PY5. These results, shown in Figure 23, indicate






FIGURE 18. POWER SPECTRA AT THE TFSO L-ARRAY FOR NOISE SAMPLE #2.




FIGURE 19. ORDINARY COHERENCE BETWEEN TFO AND PY1, PY2, PY3, PY4. NOISE SAMPLE #3.




FIGURE 20. ORDINARY COHERENCE BETWEEN PY1 AND PY2, PY3, PY4, PY5. NOISE SAMPLE #3.




FIGURE 21. ORDINARY COHERENCE BETWEEN PY2 AND PY3, PY4, PY5. NOISE SAMPLE #3.




FIGURE 22. ORDINARY COHERENCE BETWEEN PY3, AND PY4, PY5 AND BETWEEN PY4 AND PY5. NOISE SAMPLE #3.





FIGURE 23. MULTIPLE COHERENCE WITH TFO AS OUTPUT AND PY1 THROUGH PY5 AS INPUTS. NOISE SAMPLE #1 (UPPER) AND NOISE SAMPLE #3 (LOWER).

that noise sample #3 is multiply incoherent (less than about 0.6) at all frequencies, whereas noise sample #1 is highly coherent at frequencies between 0.02 cps and 0.09 cps. The low multiple coherence for sample #3 shows that there are no (or few) linear filter relations between the six elements in the array.

#### RECORDED SIGNALS

Figure 24 shows a strong Love wave recorded by the horizontal instruments at the six sites in the array. Visually, each site appears to record very closely the same signal data on all instruments.

A large teleseismic event was recorded on 13 February 1967 at about 2300Z. Program LOPSAN was used to determine the P-wave S/N improvement from beamforming. Time delays were determined by eye. The results are given below.

<u>Element</u>	<u>S/N</u>
PY1	10.70
PY2	19.90
PY4	19.21
PY5	26.79
TFO	20.50
Mean	19.42
Phased sum	42.72
db improvement	6.8
$N^{1/2}$ db	6.6




FIGURE 24. LARGE LOVE-WAVE SIGNALS RECORDED AT THE TFSO L-ARRAY.

## CONCLUSIONS

1. Ordinary coherence within the passband is high (greater than 0.8) between elements 5-10 km apart, low (less than about 0.6) between elements further apart. Noise Sample #2, however, has low coherence between all sites at all frequencies.
2. The sites PY5 and PY4 are generally incoherent with the other sites, probably due to local noise characteristics.
3. Multiple coherence is high (greater than 0.7) between 0.02 cps and 0.09 cps for Noise Sample #1 but low (less than 0.6) at all frequencies for Noise Sample #3.
4. Zero-delay RMS noise summations produce about  $N^{\frac{1}{2}}$  improvement over the average RMS noise level.
5. Beamforming produces about  $N^{\frac{1}{2}}$  improvement in signal-to-noise ratio.

## REFERENCES

Chiburis, E. F. and W. C. Dean, 1967a, "Multiple Coherence of Long Period Noise at LASA", Report No. 189, Seismic Data Laboratory, Teledyne, Inc., Alexandria, Virginia.

\_\_\_\_\_ 1967b, "Multiple Coherence of Short Period Noise at LASA", Report No. 190, Seismic Data Laboratory, Teledyne, Inc., Alexandria, Virginia.

\_\_\_\_\_ 1967c, "Multiple Coherence at 3 Vertical Arrays, UBSO, GV-TX, AP-OK", Report No. 191, Seismic Data Laboratory, Teledyne, Inc., Alexandria, Virginia.

\_\_\_\_\_ 1967d, "Multiple Coherence of Short Period Noise at UBSO and TFSO", Report No. 192, Seismic Data Laboratory, Teledyne, Inc., Alexandria, Virginia.



Unclassified

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1. ORIGINATING ACTIVITY (Corporate author)		2. REPORT SECURITY CLASSIFICATION
TELEDYNE, INC. ALEXANDRIA, VIRGINIA		Unclassified
		3. GROUP
		---
3. REPORT TITLE		
TFSO LONG-PERIOD L-ARRAY NOISE COHERENCE		
4. DESCRIPTIVE NOTES (Type of report and inclusive dates)		
Scientific		
5. AUTHOR(S) (Last name, first name, initial)		
Chiburis, E. F.		
6. REPORT DATE	7a. TOTAL NO. OF PAGES	7b. NO. OF REFS
October 20, 1967	34	4
8a. CONTRACT OR GRANT NO.	8b. ORIGINATOR'S REPORT NUMBER(S)	
F 33657-67-C-1313 A. PROJECT NO. VELA T/6702 C. ARPA Order No. 624 ARPA Program Code No. 5810	199	
	9. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
	---	
10. AVAILABILITY/LIMITATION NOTES		
This document is subject to special export controls and each transmittal to foreign governments or foreign national may be made only with prior approval of Chief, AFTAC.		
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY
---		ADVANCED RESEARCH PROJECTS AGENCY NUCLEAR TEST DETECTION OFFICE WASHINGTON, D. C.
13. ABSTRACT		
<p>Three long-period noise samples recorded at the TFSO L-array were analyzed for coherence properties. The results indicate that the ordinary coherence is generally high between elements 5-10 km apart and low between elements further apart. Multiple coherence is high for the first noise sample but low for the third sample.</p> <p>Zero-delay noise summations for an additional sample produce about <math>N^{1/2}</math> improvement over the average RMS noise level and beam-forming of a large P-wave signal produces about <math>N^{1/2}</math> improvement in signal-to-noise ratio.</p>		

DD FORM 1473  
1 JAN 64

Unclassified

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Noise Coherence						
Seismic Arrays						
Tonto Forest Seismological Observatory						

#### INSTRUCTIONS

**1. ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

**2a. REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

**2b. GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

**3. REPORT TITLE:** Enter the complete report title in all capital letters. Title in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parentheses immediately following the title.

**4. DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

**5. AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

**6. REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

**7a. TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

**7b. NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

**8a. CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

**8b, 8c, & 8d. PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

**9a. ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

**9b. OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

**10. AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

**11. SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

**12. SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

**13. ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

**14. KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical content. The assignment of links, roles, and weights is optional.